



imagePROGRAF TM-240 MFP Lm24

PERFORMANCE REIMAGINED

Reimagine performance with a sustainable 24" multifunction printer, offering less noise operation, more intuitive functionality and high print quality, to create professional quality prints with sharp, crisp lines and vivid red colour – perfect for eye-catching CAD drawings and marketing materials. Integrated scanning functionality with dedicated software boosts productivity, print and scan at speed for a more seamless workflow.

- **Integrated functionality**
Print and scan seamlessly with an easy-to-use multi-tasking device, featuring a 3" touchscreen panel on the scanner and dedicated software, for parallel processing with printing and scanning simultaneously
- **Enhanced professional quality**
The new magenta ink produces a more brilliant red and stable image enhancements mean crisper lines. Print vivid and accurate CAD drawings, posters, educational materials and more
- **Reliable productivity**
Productivity that you can count on, with reliable performance, faster processing time and a quick return from sleep mode. Save time trimming excess margins with borderless print, giving full bleed images of any size, straight from the device
- **Intuitive functionality**
Functional design with a 4.3" touch screen panel on printer, displaying intuitive instructions and important information, like media type, remaining media and ink amount. Roll paper can be replaced with ease on the flat-top cover

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF TM-240 MFP Lm24

SCANNER TECHNOLOGY

Scan technology	SingleSensor with multiple LED illumination
Maximum Resolution (dpi)	600dpi.
Scan speed	COPY 300/300dpi Draft = tips colour, 3ips mono 300/600dpi Standard = tips colour, 3ips mono 600/600dpi Best = 0.5ips colour, 1.5ips mono
Scan modes	SCAN 200dpi Draft = tips colour, 3ips mono 300dpi Standard = 0.5ips colour, 1.5ips mono 600dpi Best = 0.33ips colour, tips mono Scan to USB - RGB/Greyscale/BW, TIFF (No ScanApp) Scan to USB - RGB/Greyscale/BW, JPG, PDF, PDF/A, M-PDF (ScanApp available) Scan to PC - RGB/Greyscale/BW, Tiff, JPEG, PDF, PDF/A, TiffG4, M-PDF Copy - RGB/Greyscale/BW Copy & Archive - (Combination of Copy and Scan to PC above). Cloud connectivity is achieved by a link to Canon's Direct Print & Share. PRINT is achieved by using Canon's Direct Print & Share.
Paper Path	Face up, rear exit. Forward document transport only Document return guide(s) included
Maximum Scan Width	24" / 609.6mm
Minimum Scan Width	6.2" / 157.4mm
Maximum Document Width	26" / 660.4mm
Maximum Scan Length	109" / 2768mm
Document Thickness	Designed to scan Canon iPF printer CAD paper. Min = 0.07mm Max = 0.8mm

Scan accuracy	Accuracy 0.2% +/-1 pixel
Interface USB	USB2, 128GB FAT32.
Scan to Network	ScanApp - Sets scan directory. Minimum PC specification: • Windows 7/8/10 - 32bit. • 100Mbps Ethernet. • Intel Celeron, Core-Duo, Core-2-Duo or 2.8GHz Hyper-Threading (HT) or AMD Dual-Core processors • 2GB RAM • High speed 7,200rpm Serial ATA (SATA) HDD with minimum 2GB for applications and 20GB free for images. Suggested PC specification: • Windows 7/8/10 - 64bit. • GB Ethernet. • Intel i3,i5 or i7 processors • 4GB RAM • High speed 7,200rpm Serial ATA (SATA) HDD with minimum 2GB for applications and 20GB free for images.

Languages	ScanApp English/French/German/Italian/Spanish/Simplified Chinese/Traditional Chinese/Korean/Russian/Portuguese/Japanese/Czech/Polish
Control panel	3" touch screen display
Weight of scanner	5.28kg (11.6lbs) without Doc return guide
Dimensions (W x D x L)	Width: 935mm, Height 131mm Depth: Without Doc Return Guide - Paper tray folded: 146mm Without Doc Return Guide - Paper Tray flat: 193mm With Doc Return Guide - Paper tray folded: 206mm With Doc Return Guide - Paper Tray flat: 253mm
Compliances	Europe : CE mark, Other countries : CB certification

What's in the box?	Lm24 scanner Printer mounting brackets, fixings & 3mm tool 2 feet for desktop use 2 paper edge guides 1 Document return guides Calibration target CD for ScanApp software and PDF documentation: Lm24 Scanner User Manual per language and Quick Start Guide. Lm24 Scanner Quick Start Guide. Ethernet cable (2 meter) Power Supply Regional - Mains power cord(s) (2 meter)
---------------------------	---

PRINTER TECHNOLOGY

Printer Type	5 Colours 24"
Print Technology	Canon BubbleJet on Demand 6 colours integrated type (6 chips per print head x 1 print head)
Print Resolution	2,400 x 1,200 dpi
Number of Nozzles	Total : 15360 nozzles MBK : 5120 nozzles BK, C, M, Y: 2560 nozzles each
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.
Nozzle Pitch	1,200 dpi x 2 lines
Ink Droplet Size	minimum 5pl per colour
Ink Capacity	Bundled Starter Ink: 300ml (80ml for MBK, 55mlx4 for BK, C, M, Y) Sales Ink: 55ml (MBK, BK, C, M, Y) Pigment inks : 5 colours MBK/BK/C/M/Y
Ink Type	32 Bit: Windows7, Windows 8.1, Windows 10 64 Bit: Windows 7, Windows 8.1, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022
OS Compatibility	Apple Macintosh: macOS 10.15.7-macOS 13

Others supported job submission protocol

Printer Languages

Standard Interfaces

MEMORY

Standard memory

PRINTING SPEED

CAD Drawing

Plain paper (A1):

Poster

Plain paper (A1):

Heavy coated paper (A1)

MEDIA HANDLING

Media Feed and Output

Media Width

Media Thickness

Minimum Printable Length

Maximum Printable Length

Maximum Media Roll Diameter

Media Core Size

Margins Recommended area

Margins Printable area

Media Feed Capacity

Media Take-Up Roll Unit

Borderless Printing Width (Roll Only)

Maximum number of delivered prints

WHAT'S INCLUDED

What's in the Box?

Software Included

OPTIONS

Optional Items

CONSUMABLES

User Replaceable Items

Disclaimer

Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ® All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.
Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.

Apple AirPrint

HP-GL/2, HP RTL, JPEG (Ver. JFIF 1.02), CALS G4 (submission via FTP only)
USB A Port: N/A
USB B Port: Hi-Speed USB
Ethernet: IEEE802.3ab(100base-T), IEEE802.3u (100BASE-TX)/IEEE802.3 (10BASE-T)
Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b
*Please refer to user manual how to activate/deactivate the wireless LAN

2GB
Expansion slot : No

0:23 (Fast Economy Mode)
0:25 (Fast)
0:51 (Standard)

0:25 (Fast Economy Mode)
0:25 (Fast)
0:49 (Standard)

0:56 (Fast)
1:45 (Standard)

Roll Paper : One Roll, Upper-loading, Front Output
Cut Sheet : Upper-loading, Front Output (Manual feed using media locking lever)

Roll paper: 203.2 - 610mm
Cut sheet: 210 - 610mm

Roll/Cut : 0.07mm - 0.8mm

Roll paper: 203.2mm
Cut sheet: 279.4mm

Roll paper : 18m (varies according to the OS and application)
Cut sheet : 1.6m

150 mm

Internal diameter of roll core: 2"/3" (Optional)

Roll paper: Top: 20mm, Bottom: 3mm, Side: 3mm
Cut sheet (AppleAirPrint): Top: 20mm, Bottom: 3mm, Side: 3mm
Cut sheet (Others): Top: 20mm, Bottom: 20mm, Side: 3mm

Roll paper: Top: 3mm, Bottom: 3mm, Side: 3mm
Roll paper (borderless): Top: 0mm, Bottom: 0mm, Side: 0mm
Cut sheet (AppleAirPrint): Top: 3mm, Bottom: 12.7mm, Side: 3mm
Cut sheet (Others): Top: 3mm, Bottom: 20mm, Side: 3mm

Roll Paper: One roll
Cut Sheet: 1 sheet

N/A

[Recommended] 515mm(JIS B2), 594mm (ISO A1), 10", 14", 17", 24"
[Printable] 257mm(JIS B4), 297mm(ISO A3), 329mm (ISO A3+), 420mm(ISO A2), 515mm(JIS B3), 8", 12", 15", 16", 18", 20", 22", 300mm, 500mm, 600mm
Other than above, free size borderless printing is supported on only roll paper by user definition

Standard position - 1 sheet

Printer, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety/Standard Environment leaflet, LFP Eur Address Sheet, Important Information Sheet, Notice for PosterArtist WEB

Software available as Download from Web

Stand Basket (Simple Basket): SD-24
2"/3" Roll Holder: RH2-28
IC Card Reader Holder: RA-02

Ink Tank: M: PFI-031(55ml), MBK/BK/C/Y:PFI-030(55ml)
Print Head: PF-06
Cutter Blade: CT-08
Maintenance Cartridge: MC-31



Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2023